

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (canceled).
2. (withdrawn): A magnetic field generator as claimed in claim 1, characterized in that first ones of said plurality of magnetic segments are rotatably mounted so that their directions of magnetic fields can be altered and in that second, remaining ones of said plurality of magnetic segments are stationary magnetic segments.
3. (withdrawn): A magnetic field generator as claimed in claim 2, characterized in that the magnetic fields of said stationary magnetic segments are pointing to a circumferential direction relative to the center of said process chamber.
4. (withdrawn): A magnetic field generator as claimed in claim 2, characterized in that the magnetic fields of said stationary magnetic segments are pointing to the center of said process chamber,
5. (withdrawn): A magnetic field generator as claimed in any of claims 2 to 4, characterized in that said plurality of magnetic segments are arranged in the shape of a ring and in that a magnetic ring is provided on the outer side of said magnetic segments.

6. (currently amended): A magnetic field generator ~~as claimed in claim 1,~~
~~characterized for magnetron plasma, comprising a plurality of magnetic segments provided on~~
~~the outer side of a process chamber for performing a predetermined process on a substrate placed~~
~~in said chamber for generating a multi-pole magnetic field along the circumference of said~~
~~substrate, characterized in that the arrangement is such that a strength of said multi-pole~~
~~magnetic field in said process chamber can be controlled, and~~ in that said magnetic field
generator comprises an upper magnetic field generating mechanism and a lower magnetic field
generating mechanism and in that said upper and lower magnetic field generating mechanisms
are arranged to move vertically relative to each other.

7. (withdrawn): A magnetic field generator as claimed in claim 1, characterized in
that each of said magnetic segments is substantially in the shape of a cylinder.

8. (withdrawn): A magnetic field generator as claimed in claim 1, characterized in
that said magnetic field generator comprises an upper ring-shaped magnetic field generating
mechanism and a lower ring-shaped magnetic field generating mechanism, and each of the upper
and lower ring-shaped magnetic field generating mechanisms is provided with the magnetic
segments each of which is rotatable about an axis extending to the center of the upper and lower
ring-shaped magnetic field mechanisms,

9. (withdrawn): A magnetic field generator as claimed in claim 8, characterized in
that the arrangement is such that when the magnetic field generator is set in a first state the

circumference of said substrate is surrounded by a multi-pole magnetic field of predetermined strength and when the magnetic field generator is set in a second state the circumference of said substrate is not surrounded by a magnetic field.

10. (withdrawn): A magnetic field generator as claimed in claim 8, characterized in that said magnetic field generator comprises an upper ring-shaped magnetic field generating mechanism and a lower ring-shaped

magnetic field generating mechanism, and one or both of said upper and lower ring-shaped magnetic field generating mechanisms are arranged to rotate about the center axis of the upper and lower ring-shaped magnetic field mechanisms.

11. (withdrawn): A magnetic field generator as claimed in any of claims 8 to 10, characterized in that said magnetic field generator comprises an upper ring-shaped magnetic field generating mechanism and a lower ring-shaped magnetic field generating mechanism, and each of the upper and lower ring-shaped magnetic field generating mechanisms is provided with the magnetic segments, and the upper and lower ring-shaped magnetic field generating mechanism are arranged to move in vertically opposite directions to each other.

12. (withdrawn): A magnetic field generator as claimed in claim 8, characterized in that each of said magnetic segments is in the shape of a polygon or a circle in cross section.

13. (withdrawn): A magnetic field generator as claimed in claim 1, characterized in that a conductive ring is provided between said process chamber and said magnetic field

generator and in that said conductive ring is arranged to rotate about the center of the conductive ring.

14. (withdrawn): A magnetic field generator as claimed in claim 13, characterized in that the speed of rotation of said conductive ring is controllable.

15. (withdrawn): A magnetic field generator as claimed in claim 1, characterized in that the strength of said multi-pole magnetic field within said process chamber is controllable by varying the number of magnetic poles of said magnetic segments.

16. (withdrawn): A magnetic field generator as claimed in claim 15, characterized in that a portion of said plurality of magnetic segments is rotatable and the number of magnetic poles of said multi-pole magnetic field segments is variable.

17. (withdrawn): A magnetic field generator as claimed in claim 15, characterized in that said plurality of magnetic segments are dismountable and in that the number of magnetic poles of said multi-pole magnetic field is decreased by dismounting a portion of said plurality of magnetic segments.

18. (withdrawn): A magnetic field generator as claimed in claim 15, characterized in that a magnetic field control member is provided with between said magnetic segments and said process chamber for controlling the state of said multi-pole magnetic field in said process chamber.

19. (withdrawn): A magnetic field generator as claimed in claim 15, characterized in that said magnetic field generator comprises an upper ring-shaped magnetic field generating mechanism and a lower ring-shaped magnetic field generating mechanism, and each of the upper and lower ring-shaped magnetic field generating mechanisms is provided with the magnetic segments, and in that each of the upper and lower ring-shaped magnetic field generating mechanisms are arranged to move to vertically opposite directions to each other—.

20. (previously presented): A magnetic field generator as claimed in claim 6, characterized in that each of said magnetic segments is substantially in the shape of a cylinder.